Product Specifications Product name: Mobile Hydraulic Stretcher (CTVX)

Item	Specification	Remarks
Dimension	L 2135 mm × W 740 mm × H 560~890 mm	
Features	Backrest, Knee Gatch, Leg and Hi-Low, Trend. & Rev. Trend. Electric assisted transport.	
Materials	Steel bed, powder paint, X-Ray platform and steel guardrail	
Others	Base cover with battery storage box Base cover with oxygen cylinder holder	
Drawing	1900	
Image		
R & D Department	Supervisor Product Development Principal	

Table number: CGM-04A-09 (98.11 訂)

Date: July 10, 2014

No	Item	Specification	Accessories	Remarks
1	Bed size	L 2135 mm × W 740 mm	•	
2	Bed platform size	L 1900 mm × W 640 mm	•	
3	Side rail size	L 1200 mm × H 330 mm	•	
4	Side rail	Wave fence, plastic injection molding	•	
5	Side rail Height	Upward Side rail height 330 mmStore Side rail height 50 mm	•	
6	Platform Low-HI	560 mm ~ 890 mm	•	
7	Backrest angle	0° ~90°	•	
8	Knee Gatch Angle	$0^{\circ} \sim 40^{\circ}$	•	
9	Leg Angle	$0^{\circ} \sim 17^{\circ}$	•	
10	Trend. Rev. Trend	16° ~ -16°	•	
11	Safety Load	Max. 230kg	•	
12	IV Pole	2 sets, Located on the end of the bed, Stainless Steel, Ø22.2mm × 647~1310mm.	•	
13	IV Pole Socket	2 sets, end of the bed.	•	
14	Drainage Hook	6 sets, Located on the left and right sides of the bed.	•	
15	Constrained with fixing holes	There are 10 sets of bed designs.	•	
16	Bumper	ABS injection molding located in the corner of the bed.		
17	X-Ray Platform	Black X-Ray Board, 6 mm.		
18	Caster control	Four-step pedaling control and Steel caster.	•	
19	Casters and wheels	Central control wheel, diameter 200 mm.	•	
20	Mobile Transport	Mobile Transport Steel Wheel, Diameter 200 mm.	•	
21	Transport Handle	2 sets, Located on the end of the bed.	•	
22	Electric Power	AC 100V-240V , 50/60Hz	•	
23	Battery Back Up	Lead-acid batteries , DC24V , 4.5AH	•	
24	Electric Cable	Round wire reel, 1.8 m long, UL/3P	•	
25	Mattress	PU foam + PVC latex skin. L 1900 mm × W 650 mm × H 80 mm	0	
26	0.5m³ Oxygen Holder	Stainless steel can be installed on the head section	0	
27	Base Cover Oxygen Holder	2 pcs, Adhere to the base cover.	0	